







ROHS

SECTION A-A
Scale 2:1

NOTES:

A. Material:

1. Housing: LCP Black, thermoplastics, UL94V-0 (Halogen free)
2. Contact: Copper alloy, T=0.15mm
3. Shell: SUS, T=0.15mm

B. Finish:

1. Contact: Gold 3u" plated on contact area, 80u" min, Matte tin plated on solder tails area, 50u" min. Nickel underplating over all
2. Shell: 50u" min, Nickel underplating over all

Pin No.	Signal Name	Pin No.	Signal Name
P1	VBUS	P11	VBUS
P2	TX1+	P12	TX2+
P3	TX1-	P13	TX2-
P4	GND	P14	GND
P5	RX1+	P15	RX2+
P6	RX1-	P16	RX2-
P7	VBUS	P17	GND
P8	CC1	P18	D-
P9	SBU1	P19	D+
P10	SBU2	P20	CC2

4	Terminal	铜合金, 镀半金雾锡3u"	2SET
3	Shell	SUS, 镍50u" min	1PCS
2	Down Body	LCP, BK, 半金雾锡3u"	1PCS
1	UP Body	LCP, BK, 半金雾锡3u"	1PCS

APPROVALS		DATE	http://www.dongdudz.com	
DRAW:	ZRD	2017-12-6	TOLERANCE:	ANGLE:
CHECKED:	***	****	30≥	±0.30
APPOVALS:	***	****	10~30	±0.20
			5~10	±0.15
			≤5	±0.10
			±2°	
			MODEL: USB CONNECTOR	
			PART NO: 3.1-IDC-20P-G-AL10.9	
			UNIT :mm SCALE:1:1	
			REV: A PAGE:1/1	

